

Material Safety Data Sheet

Infosafe No™ YSXXP Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **Chewing Gum Remover**

Classified as hazardous

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Chemical Product and Company Identification Tel: (03)9416 6700 (BH)
Fax: (03)9416 8516
Web: www.peerlessjal.com.au
email: sales@peerlessjal.com.au
JAL Colour Coding: Red

Product Name Chewing Gum Remover

Company Name Peerless Jal Pty Ltd (ABN 53 006 489 345)

Address 10-12 Raglan Street Preston
Victoria 3072 Australia

Telephone/Fax Number Tel: (03) 9416 6700
Fax: (03) 9416 8516

Emergency Contact Name Peerless Jal PTY LTD

Email sales@peerlessjal.com

Recommended Use Always do a spot test on an inconspicuous area before using the product to ensure it does not damage the surface. Apply neat to affected area. Leave for three to five minutes. Scrape off softened gum using a hard plastic or metal scraper. If using on carpet, use a brush to restore pile after removing the gum.

Other Names Name Product Code

Other Information Solvent Cleaner
NOTICE: While the information contained herein is correct to the best of our knowledge, Peerless Jal Pty Ltd herein disclaims any warranties as to the accuracy of the same. Recommendations or suggestions are made without guarantee or representation as a result, since conditions of use are beyond our control. All materials are sold subject to Peerless Jal Pty Ltd standard terms and conditions of sale and on the condition that buyer shall make his/her own tests to determine the suitability of such product for buyers purposes. No statement contained herein shall be construed as a recommendation to infringe any patent.

2. HAZARDS IDENTIFICATION

Hazard Classification Classified as hazardous
HAZARDOUS SUBSTANCE.
DANGEROUS GOODS.

Risk Phrase(s) Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).
Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
Classified as hazardous
R10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R38 Irritating to skin.

Safety Phrase(s) S23(3) Do not breathe spray.
S24/25 Avoid contact with skin and eyes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization Liquid

Ingredients	Name	CAS	Proportion	Hazard Symbol	Risk Phrase
	Xylene	1330 - 20 - 7	75-100 %		
	Eucalyptus Oil	8000-48-4	30%w/v		

4. FIRST AID MEASURES

Inhalation Remove from contaminated area. Apply artificial respiration if not breathing.

Ingestion If poisoning occurs, contact a Doctor or Poisons Information Centre. Phone 13 1126. If swallowed, do NOT induce vomiting. Give a glass of water.

Material Safety Data Sheet

Infosafe No™ YSXXP Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **Chewing Gum Remover**

Classified as hazardous

Skin Remove contaminated clothing and wash skin thoroughly with water.
Eye If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.
First Aid Facilities Eyewash should be nearby and ready to use.
Advice to Doctor Treat symptomatically. If aspirated into the lungs, may cause chemical pneumonitis. Gastric lavage should only be undertaken after endotracheal intubation.

5. FIRE FIGHTING MEASURES

Specific Hazards Hazchem Code 3[Y]. Use foam, dry chemical, carbon dioxide or water fog. May produce toxic fumes of carbon monoxide.
Hazchem Code 3[Y]

6. ACCIDENTAL RELEASE MEASURES

Spills & Disposal Absorb all spills. Use Oil Spill Kit or other inert absorbent. Collect in drums.

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards The National Occupational Health and Safety Commission (Worksafe Australia) has set no exposure standards for this material. This does not imply that this material is safe or non-hazardous. There may be insufficient information available to allow the National Commission to assign an exposure standard, even on a tentative basis. Where exposure standards are available for the ingredients of this material, they are listed below.

	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³
Xylene	80	350	150	655

As published by the National Occupational Health & Safety Commission (Worksafe Australia).

TWA - the Time-Weighted Average airborne concentration over an eight-hour working day, for a five-day week over an entire working life. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

STEL is the Short Term Exposure Limit and is a 15-minute TWA exposure, which should not be exceeded at any time during a working day. Exposures at the STEL should not be longer than 15 minutes and should not be repeated more than four times per day. There should be at least 60 minutes between successive exposures at the STEL.

Exposure Standards are guides to be used in the control of occupational health hazards. They are not fine dividing lines between safe and dangerous concentrations of chemicals nor are they measures of relative toxicity. All atmospheric contamination should be kept to as low a level as is practicable.

Engineering Controls Use adequate ventilation to maintain concentrations below the exposure standards. Avoid all ignition sources. Electrical equipment must be explosion proof. Earth and bond all containers and transfer equipment.

Personal Protective Equipment Wear xylene impervious gloves and eye/face protection. If inhalation risk exists wear respirator with 'organic vapours' canister. Always wash hands before smoking, eating, drinking or using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Liquid
Appearance Clear colourless to pale yellow mobile liquid
Melting Point Not available
Boiling Point Not Available
Solubility in Water Not Miscible
Specific Gravity Approx 0.9
Vapour Pressure Not Available

Material Safety Data Sheet

Infosafe No™ YSXXP Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **Chewing Gum Remover**

Classified as hazardous

Flash Point Between 23°C and 61°C

Flammability Flammable. Use in well ventilated area. Avoid all ignition sources. Electrical equipment must be explosion proof. Earth and bond all containers and transfer equipment.

Flammable Limits - Lower Not Available

Flammable Limits - Upper Not Available

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

Health Hazard No adverse health effects expected if the product is handled in accordance with this Material Safety Data Sheet and the product label. Symptoms that may arise if the product is mishandled are: For WSA format, please refer to Health Effects Section for acute effects.

Inhalation Harmful by inhalation. May cause dizziness and nausea. May cause Central Nervous System Depression and loss of consciousness.

Ingestion May cause nausea, vomiting and diarrhoea.

Skin Harmful in contact with skin. Irritating to skin. May cause reddening.

Eye May be slightly irritating. May cause redness and stinging sensation.

Chronic Effects Prolonged or repeated skin contact may defat the skin and cause irritant contact dermatitis.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

14. TRANSPORT INFORMATION

Transport Information Classified as dangerous good according to the Australian Dangerous Goods (ADG) Code.

U.N. Number 1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

DG Class 3

Hazchem Code 3[Y]

Special Precautions for User Correct Shipping Name: Flammable Liquid, N.O.S. (Contains: Xylene)

Packaging Method 3.8.3RT1

Packing Group III

Storage and Transport This material is a Class 3 Dangerous Good and a Schedule 6 Poison. Keep out of reach of children. Store and transport according to local State or Territory Dangerous Goods and Poisons Regulations.

EPG Number 3A1

IERG Number 14

UN Number (Road Transport) 1993

Other Information This MSDS summarises our best knowledge of health and safety hazard information of the product and how to safely handle and use the product.

15. REGULATORY INFORMATION

Regulatory Information Classified as hazardous HAZARDOUS SUBSTANCE. SCHEDULED POISON.

Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).

Material Safety Data Sheet

infosafe
CS: 1.9.606

Page: 4 of 4

Infosafe No™ YSXXP Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **Chewing Gum Remover**

Classified as hazardous

Poisons Schedule

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
S6

Hazard Category

Harmful, Irritant

16. OTHER INFORMATION

Technical Contact Point

Technical Department
10-12 Raglan Street
Preston
VIC 3072.
Tel: (03)9416 6700 (BH)
Fax: (03)9416 8516

Other Information

REASON FOR CHANGE: Five Yearly Review; Update to Worksafe Format.
...End Of MSDS...

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.